

# SAFETY DATA SHEET

According to regulation according to Regulation (EC) No. 1907/2006



## SCELFAS T - POLYOL

Version 1.0 Creation date (english version): 04.03.21

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SCELFAS T - POLYOL  
Index No : Not applied  
CE No : Not applied  
CAS No : Not applied  
REACH Registration No : The product is a mixture, no need to be REACH registered.  
Product description : Composition: mixture  
Origin: organic, polyol

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Component of a Polyurethane System.  
Professional use only.

#### 1.3 Details of the supplier of the safety data sheet

Company : KEMICA COATINGS  
Address : Z.A. DU BOIS GUESLIN  
28630 MIGNIERES  
FRANCE  
Telephone : +33 (0)2 37 26 39 87  
+33 (0)2 37 26 33 56  
E-mail address of the person responsible for SDS

#### 1.4 Emergency telephone number

France : ORFILA  
Telephone : +33 (0)1 45 42 59 59  
Supplier  
Tel : +33 2 37 26 33 56 (CET : 8h30am – 12h, 13h30 – 17h)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

The product has been classified according to the legislation in force.

**Classification according to Regulation (EC) No 1272/2008 as amended.**

#### Health Hazards

Serious eye irritation	Category 2	H319: Causes serious eye irritation.
Skin sensitizer	Category 1	H317: May cause an allergic skin reaction.
Germ Cell		
Mutagenicity	Category 2	H341: Suspected of causing genetic defects.
Toxic to reproduction	Category 1B	H360FD: May damage fertility. May damage the unborn child.

Specific Target Organ Toxicity - Single Exposure	Category 1	H370: Causes damage to organs.
Specific Target Organ Toxicity - Repeated Exposure	Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
<b>Environmental Hazards</b>		
Acute hazards to the aquatic environment	Category 1	H400: Very toxic to aquatic life.
Chronic hazards to the aquatic environment	Category 1	H410: Very toxic to aquatic life with long lasting effects.

## 2.2 Label Elements

### Hazard pictograms :



#### Danger

<b>Hazard Statement(s):</b>	H319: Causes serious eye irritation. H317: May cause an allergic skin reaction. H341: Suspected of causing genetic defects. H360FD: May damage fertility. May damage the unborn child. H370: Causes damage to organs. H372: Causes damage to organs through prolonged or repeated exposure. H410: Very toxic to aquatic life with long lasting effects.
-----------------------------	---

## Precautionary Statements

<b>Prevention:</b>	P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P260: Do not breathe dust/fume/gas/mist/vapors/spray. P264: Wash thoroughly after handling. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.
--------------------	---

**Response:**

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/attention. P308+P313: IF exposed or concerned: Get medical advice/attention. P391: Collect spillage.
---

## 2.3 Other hazards

No Information.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

**3.2. Mixtures**

Hazardous components concerning CLP Regulation and relative classification :

Name	CAS No. EC No. Index No.	REACH registration No.	% [mass]	Classification [EU CLP (1272/2008)]
Dibutyltin dilaurate; dibutyl[bis(dodecanoxyloxy)] stannane	77-58-7 201-039-8 050-030-00-3	01-2119496068-27	1-3	Muta. 2 (cat. 2) Repr. 1B (cat. 1B) STOT RE 1 (cat. 1)

For explanation of abbreviations see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General advice:**

The wet and contaminated clothes and shoes need to be removed immediately.

**4.2 Description of first aid measures****Inhalation:** fresh air supply, consult a doctor if feeling unwell.**Skin Contact:** In case of contact with skin wash off with soap and water. Summon a doctor immediately.**Eye contact:** In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice**Ingestion:** Thoroughly clean the mouth with water Call for medical advice immediately; show this safety data sheet**4.3 Most important symptoms and effects, both acute and delayed:** corrosive effects sensitising effects toxic effects for reproduction mutagenic effects**4.4 Indication of any immediate medical attention and special treatment needed****Hazards:** No data available.**Treatment:** Treat symptomatically.**SECTION 5: Firefighting measures****General Fire Hazards:**

Collect contaminated firefighting water separately, must not be discharged into the drains.

foam, carbon dioxide, dry powder, water spray.

**5.1 Extinguishing media Suitable extinguishing media:****Unsuitable extinguishing media:**

High volume water jet.

In the event of fire the following can be released: - carbon dioxide, carbon monoxide - Tin oxide Under certain conditions of combustion traces of other toxic substances cannot be excluded

No specific precautions.

**5.2 Special hazards arising from the substance or mixture:**

Do not inhale explosion and/or combustion gases Self-contained breathing apparatus.

**5.3 Advice for firefighters Special fire fighting procedures:**

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures:** Use personal protective equipment. Ensure adequate ventilation.

**For non-emergency personnel:** No data available.

**For non-emergency responders:** No data available.

**responders:**

**6.2 Environmental Precautions:** Do not allow to enter drains or waterways Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up:** Take up with absorbent material (eg sand, kieselguhr, universal binder) Dispose of absorbed material in accordance with the regulations.

**6.4 Reference to other sections:** For further information on exposure monitoring and disposal see sections 8 and 13.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling:** Avoid contact with skin and eyes. Do not inhale gases/vapours/aerosols. Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid formation of aerosol.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep container tightly closed in a cool, well-ventilated place. Do not store or transport together with foodstuffs

**7.3 Specific end use(s):** No further recommendations.

**SECTION 8: Exposure controls / personal protection****8.1 Control Parameters****Occupational Exposure Limits**

Chemical name	Type	Exposure Limit Values	Source
Dibutyltin dilaurate - as Sn	TWA	0.1 mg/m <sup>3</sup>	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
	STEL 15 minutes	0.2 mg/m <sup>3</sup>	UK. EH40 Workplace Exposure Limits (WELs), as amended (01 2020)
Bis(tributyltin) oxide - as Sn	TWA	0.1 mg/m <sup>3</sup>	UK. EH40 Workplace Exposure Limits (WELs), as amended (12 2011)
	STEL 15 minutes	0.2 mg/m <sup>3</sup>	UK. EH40 Workplace Exposure Limits (WELs), as amended (01 2020)

**8.2 Exposure controls**

Chemical name	Type	Source
Dibutyltin dilaurate - as Sn	Skin designation: Can be absorbed through the skin.	UK. EH40 Workplace Exposure Limits (WELs), as amended
Bis(tributyltin) oxide - as Sn	Skin designation: Can be absorbed through the skin.	UK. EH40 Workplace Exposure Limits (WELs), as amended

**DNEL-Values**

Remarks: DNEL-Values

Critical component	Type	Route of Exposure	Health Warnings	Remarks
Dibutyltin dilaurate	Workers	Dermal	Systemic, short-term; 2.08 mg/kg bw/day	Immunotoxicity
	General population	Oral	Systemic, short-term; 0.02 mg/kg bw/day	developmental toxicity / teratogenicity
	General population	Dermal	Systemic, short-term; 0.5 mg/kg bw/day	Immunotoxicity
	General population	Dermal	Systemic, long-term; 0.16 mg/kg bw/day	Repeated dose toxicity
	Workers	Dermal	Systemic, long-term; 0.43 mg/kg bw/day	Repeated dose toxicity
	General population	Inhalation	Systemic, long-term; 0.005 mg/m3	Repeated dose toxicity
	General population	Oral	Systemic, long-term; 0.003 mg/kg bw/day	Repeated dose toxicity
	General population	Inhalation	Systemic, short-term; 0.04 mg/m3	developmental toxicity / teratogenicity
	Workers	Inhalation	Systemic, long-term; 0.02 mg/m3	Repeated dose toxicity
	Workers	Eyes	Local effects;	Low hazard (no threshold derived).
	General population	Eyes	Local effects;	No hazard identified

**PNEC-Values**

Remarks: PNEC-Values

Critical component	Environmental compartment	PNEC-Values	Remarks
Dibutyltin dilaurate	freshwater	0 mg/l	
	marine water	0 mg/l	
	Sewage treatment plant	100 mg/l	
	Predator	0.2 mg/kg	Oral

**8.2 Exposure controls****Appropriate Engineering**

No data available.

**Controls:****Individual protection measures, such as personal protective equipment**

**Eye/face protection:** Tightly fitting safety goggles

**Hand Protection:** Material: gloves made of natural latex  
Break-through time: > 60 min  
Glove thickness: 0.5 mm  
Additional Information: The protective gloves to be worn must satisfy the specifications of Regulation (EU) 2016/425 and the resulting Standard EN374. Specific workplace situations must be considered separately.  
Material: gloves made of natural latex Break-through time: > 120 min  
Glove thickness: 1 mm  
Material: gloves made of chloroprene (CR, e.g. Neoprene)  
Break-through time: > 480 min

Material: gloves made of nitril (NBR)  
Break-through time: > 480 min  
Glove thickness: 0.4 mm  
Material: gloves made of butyl (IIR)  
Break-through time: > 480 min  
Glove thickness: 0.3 mm

**Skin and Body Protection:** protective clothing

**Respiratory Protection:** in case of formation of vapours/aerosols: Short term: filter apparatus, combination filter A-P2

**Hygiene measures:** Wash hands before breaks and immediately after handling the product. Do not eat, drink or smoke when working. Remove soiled or soaked clothing immediately.

**Environmental Controls:** The environmental regulations on the control and monitoring of environmental exposures are to be observed.

## SECTION 9: Physical and chemical properties

### 9.1 Information on essential physical and chemical properties

Form:	liquid
Colour:	cream
Odour:	No odour
Odour threshold:	NA
pH:	NA
Melting point (°C):	NA
Boiling point (°C):	NA
Flash point:	>200°C
Evaporation rate:	NA
Flammability:	NA
Explosibility limit:	NA
Vapour pressure:	NA
Vapour density:	NA
Relative density:	~1,3 g/cm3 at 20 °C
Solubility in water:	Not soluble at 15 °C
Surface tension:	NA
Auto-ignition temperature:	NA
Ignition temperature:	NA
Decomposition temperature:	NA
explosive properties:	NA
Dust Explosion Class:	NA
Oxidising properties:	NA

### 9.2 Other information

<b>Explosive properties:</b>	no danger of explosion
<b>Oxidizing properties:</b>	not measured
<b>Minimum ignition temperature:</b>	not measured
<b>Metal Corrosion:</b>	not measured

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This information is not available.

**10.2 Chemical stability**

This information is not available.

**10.3 Possibility of hazardous reactions**

The product may react with strong oxidants, ammonia and some alkali metals such as magnesium, zinc or potassium

**10.4 Conditions to avoid**

Preserve away from moisture.

**10.5 Incompatible materials**

The product may react with strong oxidants, ammonia and some alkali metals such as magnesium, zinc or potassium

**10.6 Hazardous decomposition products**

No hazardous decomposition products, as long as the storage and handling requirements are met.

**SECTION 11: Toxicological Information****Information on likely routes of exposure****Acute toxicity****Oral**

**Product:** LD 50 (Rat): 2,071 mg/kg (OECD 401)

**Components:**

Dibutyltin dilaurate LD 50 (Rat): 2,071 mg/kg Based on available data, the classification criteria are not met.

Bis(tributyltin) oxide LD 50 (Rat, male and female): 127 mg/kg

**Inhalation:** If handled correctly, not a relevant route of exposure. Information on effects are given below.

**Skin Contact:** Relevant route of exposure. Information on effects are given below

**Eye contact:** Relevant route of exposure. Information on effects are given below.

**Ingestion:** If handled correctly, not a relevant route of exposure. Information on effects are given below.

**11.1 Information on toxicological effects**

# SCELFAST – POLYOL

According to regulation according to Regulation (EC) No. 1907/2006

Dibutyltin dilaurate

Version 1.0s(tributyltin) oxide Creation date (english version): 04/08/21 No data available.

## Components:

LD 50 (Rat): > 2,000 mg/kg Based on available data, the classification criteria are not met.



## Inhalation Product:

No data available.  
Not classified for acute toxicity based on available data.

## Components:

Dibutyltin dilaurate No data available., Vapour  
No data available., Dusts, mists and fumes

Bis(tributyltin) oxide

Vapour, No data available.  
Dusts, mists and fumes, No data available.

## Repeated dose toxicity

### Product:

### Components:

Dibutyltin dilaurate No data available.  
Bis(tributyltin) oxide No data available.

## Skin Corrosion/Irritation:

### Product:

not corrosive

non-corrosive Based on available data, the classification criteria are not met.

## Components:

Dibutyltin dilaurate OECD 431 (Human, reconstructed epidermis (RhE) model): Not irritating  
Based on available data, the classification criteria are not met. (Mouse):  
Irritating

## Serious Eye Damage/Eye Irritation:

Causes serious eye irritation.

## Irritation:

### Product:

### Components:

Dibutyltin dilaurate OECD 405 (Rabbit): Severe eye irritation  
Bis(tributyltin) oxide OECD 405 (Rabbit): Irritating.  
(Rabbit): Irritating. Irritating.

## Respiratory or Skin Sensitization:

May cause an allergic skin reaction.

## Sensitization:

### Product:

OECD 406 (Guinea Pig)sensitizing

## Components:

Dibutyltin dilaurate Maximization Test, OECD 406 (Guinea Pig): May cause sensitization by skin contact.

**Version** Creation date (english version):  
 1.0 04.03.21

**Product:** No data available.
**Components:**

Dibutyltin dilaurate Ames test (OECD 471): negative  
 Bis(tributyltin) oxide No data available.

**In vivo**
**Product:** No data available.
**Components:**

Dibutyltin dilaurate No data available.  
 Bis(tributyltin) oxide No data available.

**Carcinogenicity**
**Product:** Based on available data, the classification criteria are not met.
**Components:**

Dibutyltin dilaurate No data available.  
 Bis(tributyltin) oxide No data available.

**Reproductive toxicity**
**Product:** May damage fertility. May damage the unborn child.
**Components:**

Dibutyltin dilaurate Presumed human reproductive toxicant  
 Bis(tributyltin) oxide Presumed human reproductive toxicant May damage fertility. May damage the unborn child.

**Specific Target Organ Toxicity - Single Exposure**
**Product:** Thymus gland - Causes damage to organs.
**Components:**

Dibutyltin dilaurate Inhalation - vapor Oral Dermal: thymus - Category 1 Causes damage to organs.  
 Bis(tributyltin) oxide No data available.

**Specific Target Organ Toxicity - Repeated Exposure**
**Product:** Target Organs Thymus gland - Causes damage to organs through prolonged or repeated exposure.
**Components:**

Dibutyltin dilaurate Inhalation - vapor Oral Dermal: thymus - Category 1 Causes damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

According to regulation according to Regulation (EC) No. 1907/2006

## SCELFAST – POLYOL

1.0

04.03.21



## SECTION 12: Ecological Information

### 12.1 Toxicity

#### Acute toxicity

##### Fish

**Product:** LC 50 (Zebra Fish, 96 h): 3.1 mg/l (OECD 203)

##### Components

Dibutyltin dilaurate LC 50 (Danio rerio, 96 h): 21.2 mg/l (OECD 203)  
Bis(tributyltin) oxide No data available.

#### Aquatic Invertebrates

**Product:** EC 50 (Daphnia magna, 48 h): 463 µg/l (OECD 202)

##### Components

Dibutyltin dilaurate EC 50 (Daphnia magna, 48 h): 0.463 mg/l (OECD 202)  
Bis(tributyltin) oxide No data available.

#### Toxicity to Aquatic Plants

**Product:** EC 50 (Desmodesmus subspicatus (green algae), 72 h): > 1 mg/l (OECD 201)

##### Components

Dibutyltin dilaurate EC 50 (Desmodesmus subspicatus (Scenedesmus subspicatus), 72 h):  
> 1 mg/l  
Bis(tributyltin) oxide No data available.

#### Toxicity to microorganisms

**Product:** No data available.

##### Components

Dibutyltin dilaurate No data available.  
Bis(tributyltin) oxide No data available.

#### Chronic Toxicity

##### Fish

**Product:** No data available.

##### Components

Dibutyltin dilaurate No data available.  
Bis(tributyltin) oxide No data available.

#### Aquatic Invertebrates

**Product:** No data available.

##### Components

Dibutyltin dilaurate No data available.  
Bis(tributyltin) oxide No data available.

#### Toxicity to Aquatic Plants

**Product:** No data available.

# SAFETY DATA SHEET

According to regulation according to Regulation (EC) No. 1907/2006

## SCELFAST – POLYOL

1.0

04.03.21



### Components

Dibutyltin dilaurate	No data available.
Bis(tributyltin) oxide	No data available.

### 12.2 Persistence and Degradability

#### Biodegradation

Product:	Not readily degradable.
----------	-------------------------

#### BOD/COD Ratio

Product:	No data available.
----------	--------------------

#### Components

Dibutyltin dilaurate	No data available.
Bis(tributyltin) oxide	No data available.

### 12.3 Bioaccumulative potential

Product:	No data available.
----------	--------------------

### 12.4 Mobility in soil:

### 12.5 Results of PBT and vPvB assessment:

Dibutyltin dilaurate	Non-classified vPvB substance Non-classified PBT substance
Bis(tributyltin) oxide	Non-classified vPvB substance PBT substance

### 12.6 Other adverse effects:

The product is classified as highly hazardous to waters (according to the German Regulation on the Classification of Substances Hazardous to Waters (WwSV)). Do not allow to enter soil, waterways or waste water canal.

## SECTION 13: Disposal considerations

Elimination must be carried out in compliance with all decrees, statutes and laws in force at the local, national and international levels. For disposal within the EU, use the waste code in force, according to the European Waste Catalog (EWC).

### 13.1 Waste treatment methods

After complete emptying (no drainage or dripping, troweling) empty packaging may be offered for recycling, according to the specification in force for packaging, at the receiving stations of the chemical industry's return systems. Recycling must comply with national legislation and regulations concerning the protection of the environment.

Do not throw away on wastewater.

## SECTION 14: Transport information

### 14.1 UN number

ADR	:	UN 3082
RID	:	UN 3082
IMDG	:	UN 3082
IATA	:	UN 3082

### 14.2 UN proper shipping name

ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibutyl tin dilaurate)
RID	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

# SAFETY DATA SHEET

According to regulation according to Regulation (EC) No. 1907/2006

## SCELFAST – POLYOL

1.0

04.03.21



N.O.S.  
(Dibutyl tin dilaurate)

### IMDG

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.

### IATA

#### 14.3 Transport hazard class(es)

(Dibutyl tin dilaurate) : Environmentally hazardous substance, liquid, n.o.s. (Dibutyl tin dilaurate)

ADR : 9  
RID : 9  
IMDG : 9  
IATA : 9

#### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)  
  
**RID**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
  
**IMDG**  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Remarks : IMDG Code segregation group 7 - Heavy metals and their salts (incl. their organometallic compounds)

#### IATA (Cargo aircraft only)

Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : 9MI

#### IATA (Passenger and cargo aircraft)

Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : 9MI

#### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : yes

#### RID

# SAFETY DATA SHEET

According to regulation according to Regulation (EC) No. 1907/2006

## SCELFAST – POLYOL

1.0

04.03.21



Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

### IATA (Passenger and cargo aircraft)

Environmentally hazardous : yes

### IATA (Cargo aircraft only)

Environmentally hazardous : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

#### EU Regulations

#### Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

The packaging shall be visibly, legibly and indelibly marked as follows:  
Restricted to professional users.

Chemical name	CAS-No.	Concentration
Dibutyltin dilaurate	77-58-7	100%
Bis(tributyltin) oxide	56-35-9	- <0.1%

#### EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:

Classification	Lower-tier Requirements	Upper-tier Requirements
E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100 t	200 t

### 15.2 Chemical safety assessment:

A substance safety assessment was carried out for this product.

## SECTION 16: Other information

### Full text of hazard statements (H) and precautionary statements mentioned in sections 2, 3 and 10 of the CLP classification (1272/2008 / EC).

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.

# SAFETY DATA SHEET

According to regulation according to Regulation (EC) No. 1907/2006

## SCELFAST – POLYOL

1.0

04.03.21



H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H360Df	May damage the unborn child. Suspected of damaging fertility.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to organs through prolonged or repeated exposure by ingestion.
H372	Causes damage to organs through prolonged or repeated exposure by inhalation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Printing date : 05/03/2021

Version : 1.0 – creation, – SDS According to regulation according to Regulation (EC) No. 1907/2006 (REACH)

### Advice for the reader

**While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.**

**IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.**

**THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.**

**Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.**

**SOUPLETHANE is a registered trademark of KEMICA COATINGS in one or more countries, but not all countries.**

**NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED KEMICA COATINGS EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR KEMICA COATINGS PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM KEMICA COATINGS ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO KEMICA COATINGS AT THE ABOVE ADDRESS.**